
Product Data Sheet - DivideWall







	ANGLE 90	ANGLE 45
TOP/BOTTOM PROFILE	31 x 110 x 740 mm 31 x 110 x 1340 mm 31 x 110 x 1940 mm 31 x 110 x 2540 mm	31 x 110 x 810 mm 31 x 110 x 1410 mm 31 x 110 x 2010 mm 31 x 110 x 2610 mm
DIMENSIONS	Lamella profiles: 31 x 100 x 3000 mm Top profile milling: 15mm Bottom profile milling: 5mm	Lamella profiles: 31 x 100 x 3000 mm Top profile milling: 15mm Bottom profile milling: 5mm
NUMBER OF LAMELLAS FOR DIFFERENT WIDTHS	740mm: 8 pcs. lamella 1340mm: 14 pcs. lamella 1940mm: 20 pcs. lamella 2540mm: 26 pcs. lamella	810mm: 8 pcs. lamella 1410mm: 14 pcs. lamella 2010mm: 20 pcs. lamella 2610mm: 26 pcs. Lamella
TOTAL WEIGHT(1)	740mm: 45 kg 1340mm: 79 kg 1940mm: 113 kg 2540mm: 147 kg	810mm: 46 kg 1410mm: 80 kg 2010mm: 114 kg 2610mm: 148 kg
TOLERANCES	Thickness: ± 0,2mm Weight: ± 10%	Thickness: ± 0,2mm Weight: ± 10%
SURFACE TREATMENT	Oiled/Untreated/Painted	Oiled/Untreated/Painted
FORMALDEHYDE	E1 ⁽⁴⁾	E1 ⁽⁴⁾
CERTIFICATIONS	FSC® - C191539	FSC® - C191539

NATURAL MATERIALS

An I-Wood Denmark® panel is a natural product in the best and most classic sense of the word. Sorting will therefore always be reflected in the natural character of the wood. Each piece of wood has its own expression and unique grain. Therefore, you can expect variation in the colour and expression of the wood. Our pictures are indicative.

TEMPERATURE

I-Wood Denmark® DivideWalls must be stored in a dry, warm, plain place. This will ensure a safe, consistent humidity level of approx. 4-10%. The room where your new wood panels are to be installed must also be dry and warm – and heated to approx. 17-21 degrees. We recommend a humidity level of about 30-60%.

MAINTENANCE

I-Wood Denmark® products require minimal maintenance, as they are natural products. We simply recommend dusting the products as needed. Natural products can over time vary in expression and colour depending on the individual product and environment.

